

Firmware-Features

Profi Line Fast Ethernet (FE) and Gigabit Ethernet (GBE) Industrial Switches

1 IP Stack		
1	IPv4 Stack	Internet Protocol v4 handling with support of IPv4, ARP, DHCP, ICMP.
2	IPv4 Standard	RFC 791 (IPv4), RFC 826 (ARP), RFC 792 (ICMP), RFC 2131 (DHCP)
2 Port Control		
1	Administration	Port disable, Individual port alias
2	Ethernet TP	Auto-Negotiation, speed, duplex mode, flow-control, Auto MDI/MDI-X
3	Ethernet Fiber / SFP (SFP: GBE only)	Speed, duplex mode, flow-control
3 Power-over-Ethernet (PoE)		
1	Function	Sourcing of power to connected devices via standard network Twisted-Pair cable
2	802.3af mode	PoE voltage is turned on only after powered device (PD) is detected and classified on port. Output voltage and power is monitored. Port power is shut down if limits are exceeded.
3	Power Management	Power limit can be defined per port and per total device. Additionally the class of the powered device (PD) can be limited per port.
4	Standards	IEEE Std. 802.3af (Data Terminal Equipment Power via Media Dependent Interface)
4 Switch Functions		
1	Port Monitor	Monitor port for the connection of a network protocol analyser. Traffic of the port to be analysed is copied to the monitor port.
2	RMON counters	17 Integrated counters for detailed traffic analysis and network trouble shooting.
3	MAC Table	Access to table of MAC addresses learned by the switch. Can be filtered per port, VLAN address type and entry type (dynamic/static).
5 Virtual LANs (VLANs)		
1	Function	Logical structuring of physical networks by adding a Virtual LAN ID (VID) to each Ethernet packet. Incoming packets are filtered and forwarded according to their VID. Each port can be configured for Access, Hybrid or Trunk VLAN processing mode. Independent VLANs (16) out of the full range of 1 to 4095 can be filtered per device.
2	Access Mode	For the connection of non-VLAN capable end devices (e.g. PCs). Outgoing packets are send untagged. Incoming packets are tagged with the port default VLAN ID (PVID).
3	Trunk Mode	For the interconnection of VLAN capable switches. Outgoing packets are always send tagged. Incoming packets are received tagged. Incoming packets without VLAN tag are tagged with the port default VLAN ID (PVID).
4	Hybrid Mode	For the connection of VLAN capable and non-VLAN capable devices on the same port (e.g. VoIP-phone (tagged) and PC (untagged)). Outgoing packets are send tagged, except packets for the port default VLAN ID (PVID), which are untagged. Incoming packets are received untagged for the port default VLAN (PVID), all other packets are tagged.
5	Voice VLAN	VLAN ID used by LLDP/CDP to assign VLAN to connected VoIP-phone.
6	RSTP VLAN	VLAN ID used by Spanning Tree instance for BPDU tagging.
7	Unauthorized VLAN	VLAN ID assigned by Port Based Access Control to unauthorized ports (guest VLAN).
8	Management VLAN	VLAN ID used by the management agent (device internal port).
9	Standard	IEEE Std. 802.1D, IEEE Std. 802.1Q, IEEE Std. 802.1p

6 Quality of Service (QoS)		
1	Priority Queues	4 priority queues per port.
2	Prioritization Scheme	Strict priority (higher priority always first) or weighted fair queuing (8:4:2:1 highest to lowest).
3	Layer1 Priority	Static priority queue can be assigned for each port.
4	Layer2 Priority	Incoming packets are forwarded according to the priority code point in their VLAN tag. The 8 VLAN priority code points can be individually mapped on the 4 priority queues.
5	Layer3 Priority	Incoming packets are forwarded according to the value of the DiffServ Codepoint (IPv4) in their IP header. Maximum 64 codepoints are supported. For each code point the corresponding priority queue can be mapped.
7	Standard	IEEE Std. 802.1p (VLAN priority code point), RFC 2474/3260 (IPv4 DiffServ/IPv6 Traffic Class)
7 Spanning Tree Protocol		
1	Rapid Spanning Tree (RSTP)	Automatic detection of loops and redundant network paths. Single STP instance running in configurable VLAN. Rapid Spanning Tree Protocol (RSTP) backwards compatible to Spanning Tree standard (STP).
2	Standard	IEEE Std. 802.1D-2004
8 Ring-Protocols		
1	MS-Ring Protocol (devices with ring function, only)	MICROSENS Ring-Protocol for Fault tolerant fiber ring with reconfiguration < 20 ms
9 Multicast Forwarding		
1	IGMP Snooping	Snooping of Internet Group Management Protocol (IGMPv1/v2/v3) for IPv4. Automatic detection and forwarding of IPv4 multicast-streams. Unregistered packets can be flooded or blocked. Multicast routers can be detected by discovery or by query message.
2	Standard	RFC 4541 (IGMP)
10 Real Time Clock (RTC)		
1	Function (FE only)	Internal device clock can be synchronized with external NTP server.
2	Protocol (FE only)	Simple Network Time Protocol (NTP)
3	Standard (FE only)	RFC 4330 (NTP)
11 Cisco Discovery Protocol (CDP)		
1	Function	CDP v1, v2 for automatic detection of capabilities of neighbor CDP enabled devices.
2	Voice VLAN	Support of Voice VLAN for configuration of connected Cisco VoIP-phone.
12 Port Access Control		
1	Function	Port-Based Network Access Control with dynamic port VLAN support and fallback to MAC based authentication methods. Network access is controlled at the port level. Supports IEEE Std. 802.1X Authentication, RADIUS MAC Authentication, MAC Locking and forced authorized/unauthorized mode.
2	Communication	EAPOL, RADIUS
3	Authentication Protocols	EAP-MD5, EAP-PEAP (inner protocol: MSCHAPv2), EAP-TLS, EAP-TTLS (inner protocols: EAP-MD5, EAP-TLS, PAP)
4	IEEE 802.1X Authentication	Multiple users can be authenticated using central RADIUS server based on username/password or certificate.
5	RADIUS MAC Authentication	Multiple users can be authenticated using central RADIUS server based on their MAC addresses.
6	MAC locking	Multiple users can be authenticated based on their MAC addresses. Authorized MAC addresses are stored permanently in the device. They can be configured manually or automatically by locking the first MAC addresses learned on the port.
7	Dynamic VLAN	RADIUS server can provide user specific VLAN ID using tunnel-attribute in accept message. Port VLAN is dynamically set accordingly. Unauthorized users may be placed in an unauthorized VLAN ('guest VLAN') or blocked completely.
8	Standard	IEEE 802.1X-2004 (Port-Based Network Access Control).

13 Command Line Interface (CLI)

1	Function	Intuitive command-set with auto-complete and redo-buffer. Individual console prompt string, Console inactivity timeout. Supports full scripting and editing of script files. Supports color displays. Permits offline configuration as well as management of an unlimited number of user configuration sets (limited by system memory constrains only).
2	Telnet	Telnet via TCP/IP port 23.
3	Secure Shell (SSH) (FE only)	SSH via TCP/IP port 22. Authentication methods RSA, Diffie-Hellman Key Exchange. Encryption protocols 3DES-CBC, HMAC-SHA1.

14 Web Manager

1	Function	Integrated Web Manager with graphical user interface (GUI) for device configuration and administration using standard web browser.
2	Protocol	HTML v4.01, HTTP, Java Script
3	Browser compatibility	Firefox 4.x, IE 8.x, Javascript support required.

15 Simple Network Management Protocol (SNMP)

1	SNMPv1/v2c	Simple Network Management Protocol v1, v2c (SNMPv1, v2c) to access device information stored in Management Information Base (MIB). Security provided by community strings for Set/Get commands and optionally by G6 login scheme.
2	Traps (SNMPv1/v2c)	Traps, Notifications sent to unlimited number of independently configurable receiver destinations (limited by system memory constrains only). Sending of message is triggered by internal device status change events. Event triggers can be configured individually per destination. Test function to trigger Trap/Notification for simplified configuration check (Web Manager and CLI only).
5	MIBs	MIB-2, Enterprise-MIB. File can be downloaded from the integrated Web Manager.
6	Standard	RFC 1155/1156/1157 (SNMPv1), RFC 1901/1905/1906 (SNMPv2)

16 RADIUS Client

1	Function	RADIUS client via UDP/IP ports 1812 (access), 1813 (accounting) for Remote Authentication Dial In User Service (RADIUS) server for authorizing user access and logging of user accounting information.
2	Redundancy	In case of a response timeout, the next RADIUS server is requested.
3	Standard	RFC 2865 (RADIUS), RFC 2866 (Accounting), RFC 2868 (Tunnel Attributes)

17 Files

1	Firmware Update	Firmware update by management-software (NMP) or web-manager.
---	-----------------	--

18 Syslog Client

1	Function	Syslog messages are triggered by system events and can be send to max 4 Syslog servers (limited by system memory constrains only).
2	Standard	RFC 5424

This document in whole or in part may not be duplicated, reproduced, stored or retransmitted without prior written permission of MICROSENS GmbH & Co. KG. All information in this document is provided 'as is' and subject to change without notice. MICROSENS GmbH & Co. KG disclaims any liability for the correctness, completeness or quality of the information provided, fitness for a particular purpose or consecutive damage. MICROSENS is a trademark of MICROSENS GmbH & Co. KG. Any product names mentioned herein may be trademarks and/or registered trademarks of their respective companies. 09/13pk