

# BL980

**4K Network bullet camera, 4-8mm motorized, H.265/H.264/MJPEG**

## DESCRIPTION

The BL980 is an 8MP HD bullet camera with built-in IR illumination providing razor sharp 4K images even under difficult lighting conditions. Its unique cable-managed bracket, built-in IR, weather and vandal resistance, makes it the ideal camera for almost any outdoor application. As underlined by its ONVIF Profile Q conformance, installation is fast and easy.

## FEATURES

---

4K resolution, 8 MP @ 30 fps

---

4-8 mm motorized varifocal lens

---

Quad-stream H.265, H.264 and MJPEG video

---

120 dB High Dynamic Range

---

Built-in IR illuminator

---

IP66 ingress protection

---

IK10 impact rating

---

24 Vac, 12 Vdc, PoE

---

ONVIF Profile S, G and Q

---



## Description

### Multi-stream multi-codec

The camera has quad-stream capability for simultaneous streaming of H.265, H.264 and MJPEG. Multiple combinations of resolution, frame rate, and encoding can be configured to fit all possible live viewing and recording scenarios. The 4K or 8 Mpixel resolution is available at 25/30 fps still offering multiple exposure WDR (or HDR, in short) with the possibility to add a second stream.

### Built-in IR illuminator

With a working distance of up to 40 m the camera has its own IR illumination built-in. The intelligent lighting control make sure that under every condition the exposure on the subjects and surroundings is nicely balanced

### Open standards

Multiple options are available to easily integrate the BL980 to a video management system. In support of open standards, the camera is compliant with the ONVIF Profile Q for out of the box installation, profile G from local recording and profile S for streaming and VMS compatibility.

### Image enhancement

The BL980 utilizes advanced image processing technology. Crisp and detailed 4K images with an extremely high dynamic range in real time due to multiple exposure HDR within one frame. Back-light and High-light compensation enhances image-visibility in difficult lighting situations. In addition the camera provides for 3D motion compensated noise reduction for the best images.

### Power source choices

The BL980 can be powered by 12 Vdc, 24 Vac, or over the network with PoE.

Camera			
Image sensor	1/1.8" CMOS		
Effective pixels	3864(H) x 2180(V)		
Minimum scene illumination	0.04 Lux color, 0.002 Lux B/W, f/1.6		
	0 lux with IR		
Shutter speed	1 to 1/10.000 sec		
IR illumination	850 nm, up to 40 m		
IR function	Auto, Night, Day, Light sensor, Light On, Light Off, Smart		
Lens	Motorized varifocal		
Focal length	4 to 8 mm, f/1.6		
Horizontal field of view	113° (Wide) to 59° (Tele)		
Lens material	High-grade optical glass		
Image control			
Dynamic range	120 dB (HDR)		
Exposure control	P-Iris		
White balance	Auto, ATW, One push, Manual		
Image settings	Sharpness, Brightness, Contrast, Color, EV, Backlight Compensation, Highlight Compensation, WDR		
SNR	Better than 54dBw		
Noise reduction	2DNR, 3DNR, motion compensated noise reduction		
Image rotation	90°, 180°, 270° rotation		
Digital zoom	10x		
Functions			
Privacy masks	8 colors, 5 masks		
Text and picture overlay	Date, time, date & time, subtitle, image		
Video motion detection	On / off / by schedule		
Video motion detection alarm	Alarm output, record video clip, send alarm message, upload image		
Network failure detection	On / off / by schedule		
Network failure detection alarm	Alarm output, record video clip, send alarm message, upload image		
Tamper detection	On / off / by schedule		
Tamper detection alarm	Alarm output, record video clip, send alarm message, upload image		
Behavior Analytics	Intrusion, Loitering Detection, Object Abandoned, Object Removal, Camera Sabotage, Wrong Direction, Object Counting		
Video			
Compression algorithm(s)	H.265, H.264, MJPEG		
Number streams	4x, individually configurable H.265/H.264/MJPEG streams in resolution, frame rate and bandwidth.		
Supported resolutions	3840x2160, 3200x1800, 1920x1080, 1280x1024, 1280x720, 1024x768, 800x600, 720x480, 640x480, 352x240		
Max streaming (H264/H265/MJPEG)			
60fps	1920x1080	1920x1080	352x240

## Specs

Video				
30fps (HDR)	3840x2160	800x600		
30fps (HDR)	3200x1800	1920x1080	800x600	
30fps (HDR)	1920x1080	1920x1080	1920x1080	1920x1080
Compression bit rate control	Constant bit rate (CBR), variable bit rate (VBR), Low bit rate (LBR)			
Max frame rate MJPEG	1080p (1920x1080) @ 30 fps			
Compression bit rate control	Low bit rate (LBR), constant bit rate (CBR), variable bit rate (VBR)			
Output bit rate (per stream)	Up to 10240 kbit/s			
Number of clients	Up to 20 (RTSP)			
Total output data rate (max)	50000 kbit/s			
Audio				
Two-way audio	Line in, Line out			
Compression	G.711 ( $\mu$ -law, a-law) / G.726 / AAC / LPCM			
Input level, Output level	Adjustable gain			
Connector type	Female phone jacks, 3.5 mm on breakout cable			
Alarm inputs/output				
Input	2			
Output	1			
Connector type	Terminal block on breakout cable			
Storage				
Storage options	Supports up to 512 GB capacity of SD/SDHC/SDXC memory (vFAT/EXT4)			
Network storage	NAS			
Network				
Interface(s)	100/1000 Mb Ethernet			
Network protocols	IPv4/v6, TCP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SNMP, SMTP, DHCP, UPnP, PPPoE, IGMP, IEEE 802.1x, QoS			
Connector type	RJ-45 on breakout cable			
Management				
Supported browsers	Internet Explorer 9, 10 and 11 (limited support for Edge, Chrome, Firefox, Safari)			
Security	HTTPS, IP Filter, IEEE 802.1x, digest authentication			
Protocols	UPnP, SNMP, ONVIF Profiles S, G, and Q, Siqura API			
Password levels	User and Administrator			
User accounts	20			
Powering				
Power consumption	Max. 13.68 W			
Power	24 Vac / 12 Vdc / 802.3af PoE class 0			
Connector type	1x 3 Pin terminal block on breakout cable			

# Specs

**Powering****Environmental**

Operating temperature	-55°C to 60°C (-67°F to 140°F)
Relative humidity	10% to 100%, with condensation

**Mechanical**

Dimensions	diameter 92 x 220 mm
Weight	780 g
Color	RAL 9003 (Signal white)
Ingress protection	IP66
Impact rating	IK10

**Ordering information**

BL980	4K Network bullet camera, 4-8mm motorized, H.265/H.264/MJPEG
-------	--

**Accessories**

JB07/BL	Junction box for BL8xx
PM09B/BL	Pole mount junction box for BL8xx