

BC950

5MP box camera, C/CS-mount, H.265/H.264/MJPEG, ABF

DESCRIPTION

Preliminary Datasheet The BC950 is an 5MP HD box camera with built-in auto back-focus providing razor-sharp 5MP images even under difficult lighting conditions. The camera has multi-stream capabilities for simultaneously streaming of H.265/H.264/MJPEG. Multiple combinations of resolution and frame rate can be configured. To have a secured network environment, BC950 is capable of streaming out by HTTPS protocol as well as SRTP protocols.

FEATURES

Max 5MP 30fps, 1080p 60fps

Quad stream H.264, H.265 and MJPEG

Secured Streaming SRTP

CS mount with selected lens

Auto back focus (ABF)

Embedded Video analytics

Built-In Gyro, EIS

ONVIF Profile S, G and T



Specs



Analytics

	Object Removal
Event detections	External Input, Periodical Event, Tampering, Audio Detection, Manual Trigger, System boot, recording notification
Event Action	Alarm output, Record video clip to NAS/SD card, Send alarm message and image by E-mail/FTP, Send HTTP notification

Audio

Capability	Two-way stereo audio
Audio Interface	1x 3.5 mm audio in (line in) ; 1x 3.5 mm audio out interface
Compression	G.711, G.726, AAC, LPCM

Data

Serial port	RS-485, 2-wire terminal block
Protocols	Pelco D, Pelco P

Alarm

Input	2x
Output	2x
Operational modes	Motion detection, Tampering alarm, Alarm I/O

Network

Communication Interface	10/100 Mb (RJ45)
Network protocols	IPv4/IPv6, HTTP, HTTPS (TLS1.2), 802.1x, Qos, FTP, SMTP(SSL), UPnP, SNMP(v1/v2/v3/Traps), DNS, DDNS, NTP, RTSP, RTCP, RTP/UDP, TCP/IP, IGMP(v2/v3), DHCP, PPPoE, SSL/TLS, SRTP, ONVIF Profile S/G/T, Siquira Protocol
Security	User authentication, Privilege Management, Syslog, Digest authentication (RTSP, HTTP), HTTPS encryption (TLS1.2); IEEE 802.1x port-based network access control, IP filtering, signed firmware, secured bootup
Web Viewer	Internet Explorer 11, Microsoft Edge, Google Chrome, Mozilla Firefox


General

Material	Die cast aluminum and Plastic
Edge Storage	Built-in micro SD/SDHC/SDXC slot, up to 512 GB
Power	AC24V, 12 Vdc (terminal block), IEEE 802.3af PoE Class 0, Max. 9.11W
Operating temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Relative Humidity	+5% to 100%
Dimensions(camera body)	150x82x52 mm
Weight	395g
Color	RAL 7037, RAL9005

Ordering Information

BC950	5MP box camera, C/CS-mount, H.265/H.264/MJPEG, ABF
-------	--

DIMENSION IN MM



RELATED



Siqua Fixed Camera Accessories
Mounting kits for fixed dome and bullet camera



Siqua HSG04
Outdoor Wiper housing for a fixed box camera



Siqua HSG02LV
Outdoor housing for a fixed box camera



Siqua Lenses
Megapixel Varifocal Lenses



Siqua XSNet 3100EoC
10/100/1000Base-TX Ethernet over Coax Adapter



Siqua XSNet 3100EoC
10/100/1000Base-TX Ethernet over Coax Adapter



Siqua XSNet C3100MC
Hardened 10/100Base-TX to 100Base FX Media Converter



TKHSecuritySolutions XSNet C4104 SW
4-port + 2-port switch



Siqua XSNet C4108 SW
8+2-Port field-hardened Gigabit Ethernet switch



TKHSecuritySolutions XSNet S4104 SW
4 + 2-Port Fast Ethernet switch



Siqua XSNet S4108 SW
8+2-Port Gigabit Ethernet switch



Siqua XSNet C4208 SW PoE v2
8+2-Port Gigabit Ethernet switches with PoE

TKHSecuritySolutions XSNet C6108 SW
8+4-Port field-hardened Gigabit Ethernet switch

