
VDG NVH-2524XR

Video server 19", 4U, 24 bay HS, Xeon, SSD, RAID, RPSU

Description

The NVH-2500 series are powerful, customizable, stackable and rack-mounted VDG servers. It combines top quality components and a user-friendly configuration to deliver high-power output and reliability. It's casing and components are engineered to ensure an optimized airflow (even when stacked) for higher efficiency, which results in lower energy consumption. Its redundant power supply ensures a continuous operation at all times.

Built as stand-alone servers, the NVH-2500 series' front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs.

The reliability is ensured through a standard RAID 5 configuration and redundancy, but can be configured otherwise if necessary. Optionally, a hot-standby hard-drive can be configured to ensure maximum reliability and reduce service needs. The NVH-2524XR contains 24 slots for hard-disk storage.

Features

- 4U Rack-mountable Server Chassis
- 24x 3.5" hot swappable HDD bays
- Standard RAID 5 configuration
- 875W Redundant Power Supply
- 1x 24-Port 12G Mini-SAS HD Expander Backplane
- Front access info tag for easy server management
- Slide rail

Optional expansions:

- VDG Video server storage
- NVH-GBLAN for 1 extra Ethernet connection port
- Ethernet server adapter fiber



Specs

System

Operating system	Microsoft Windows 10 Pro 64-bit
Hard disk	64GB SSD (included)
Recording storage capacity	Up to 240TB (3.5" hard disk drives)
Raid configuration	Standard Raid 5 configuration Except Raid 1 configuration with 2 hard drives
Effective recording storage capacity	230TB (after Raid 5)
Processor	Intel Xeon E3 processor
Memory	16GB memory
Network Interface	Dual Gigabit Ethernet RJ-45 (10/100/1000 MB/s)
Video output	VGA

Mechanical

Form Factor	19-inch rackmount
Dimensions (DxWxH)	698mm x 432mm x 176mm (27.5" x 17" x 6.9")

Electrical

Power Input	100-240VAC,50/60Hz,10-8A
Power Supply	875W Redundant

Environmental

Operating Temperature	5° C - 40° C (41°F - 104°F)
Storage Temperature	-40° C - 65° C (-40°F - 149°F)

Ordering Info

NVH-2524XR	Video server 19", 4U, 24 bay HS, Xeon, SSD, RAID, RPSU
------------	--

VDG Server accessories

NVH-GBLAN	Extra 100/1000Mbps LAN interface
NVH-I350F2	Ethernet server adapter fiber
NVH-81TB	Basic video server storage 1TB (incl. assembly and config)
NVH-82TB	Basic video server storage 2TB (incl. assembly and config)
NVH-83TB	Basic video server storage 3TB (incl. assembly and config)
NVH-84TB	Basic video server storage 4TB (incl. assembly and config)
NVH-86TB	Basic video server storage 6TB (incl. assembly and config)
NVH-88TB	Basic video server storage 8TB (incl. assembly and config)
NVH-810TB	Basic video server storage 10TB (incl. assembly and config)
NVH-92TB	Pro video server storage 2TB (incl. assembly and config)
NVH-94TB	Pro video server storage 4TB (incl. assembly and config)
NVH-96TB	Pro video server storage 6TB (incl. assembly and config)
NVH-98TB	Pro video server storage 8TB (incl. assembly and config)
NVH-910TB	Pro video server storage 10TB (incl. assembly and config)