

Tattile

ANPR Mobile

Automatic Number Plate Reader

Mobile

is the smart solution to prevent crime, offered as an aid to Police Forces. It is an evolved and modern license plate reading system, installed on the cars of specialized operational departments and/or intelligence services, as a support to surveillance and protection, serving as a tireless watchful eye on the road.

29333

ANPR Mobile is the latest generation system with Megapixel sensors that can scan up to 60 license plates per second, front and rear, in any light condition. It is part of the sophisticated Tattile ANPR/*ALPR* (Automatic Number Plate Reader) All On Board camera family, to read license plates in movement.

Wi-Fi data transmission from the unit to the pc/tablet

Embedded licence plate analysis (OCR on board)

Police Enforcement - Crime Prevention

Software Features

	ANPR Mobile	
Licence Plate Recognition		
OCR	ANPR (ALPR) engine on board	
Capture rate	Up to 60 fps	
Configuration		
Web Server	Installation and configuration by Web Server on board	
TCP/IP Server	Configuration and monitoring through TCP/IP protocol	
Date and Hour	Synchronization via SNTP protocol or GPS	
Software Update	Upgrading via Web Interface and SDK	
Data Transmission		
FTP	FTP Client to FTP Server mode for remote data transmission; two IP address management	
TCP/IP	Tattile TCP/IP open protocol; two IP address management	
Streaming	Video streaming via standard RTSP protocol	
Operating Mode		
Free Run	Continuous processing with automatic plate detection	

Technical Data

	ANPR Mobile	
System		
ANPR (ALPR) camera	1920 x 1080 Monochrome CMOS sensor	
Context camera	1920 x 1080 Color CMOS sensor	
Illuminator	Short range: 6 LEDs High power infrared @ 850nm	
	Medium/long range: 10 LEDs High power infrared @ 850nm	
Lenses	C-Mount. Many focal length available	
Operating System	Linux	
Connectors	Waterproof circular connector	
Network	Fast Ethernet 10/100 and WiFi 802.11 b/g/n	
Storage	Up to 128 GB	
Environment, Size, Power		
Operating & Storage Temperature	From -30° to +60° C / -22° to +140° F	
Operating & Storage Humidity	Up to 95% non condensing	
Dimensions	178 x 76 x 141 mm - 7 x 3 x 5.5 in (WxHxL)	
Weight	1,650 Kg - 3.63 lbs	
Protection	Waterproof IP66/IP67	
Power supply voltage	12 Vdc	
Power consumption	15 W	

Part Numbers

ANPR Mobile	
F01710	ANPR MOBILE SYSTEM short range
F01845	ANPR MOBILE SYSTEM medium range
F01696	ANPR MOBILE SYSTEM long range