



RayTec PSU-VAR-20W

External PSU for Vario i2, 24V, 20W, 1xO/P, IP66

Description

The VARIO series of Power Supply Units (PSU) is purpose designed to correctly power all VARIO illuminators including VARIO IP, and provides a platform for the easiest, quickest and safest wiring and installation. As a full product family, there is a PSU to power any VARIO illuminator. The VARIO PSU 20W requires a 100-230V AC input and provides 24V output. 20W.

Features

- Powers all VARIO illuminators including VARIO IP
- Powers multiple VARIO illuminators from one PSU
- 'Fast-Connect' easy wiring for all VARIO input and output connections
- Internal illumination for night time installation
- High Quality IP66 Aluminium Enclosure
- Automotive blade output fuses fast and easy sourcing and replacement
- Provides correct power for all VARIO illuminators
- Slowblow input fuse replaceable without disconnecting mains input
- Status indicators signify correct voltage



Specs

Illuminators (standard)	1x VARIO 2 series plus aux output (max 8W)
Input	100-230V AC
Input Fuse Type	20mm, slowblow, user replaceable without disconnecting mains input
Input Fuse Rating	1A
Max Output	20W
Output for VARIO Illuminators	1 for VARIO 2 series
Output Fuse Type	automotive, blade, user replaceable
Output Fuse Rating	3A
FastConnect wiring	Quick and easy wiring for VARIO input and output connections - 4 way robust
	terminal for telemetry input and photocell following output
White Light status LEDs	White-Light LED status indicators on all fused outputs to indicate correct voltage and
	to provide support illumination during installation and maintenance
Cat5 Connector	N/A
Glands	2x M16, 2x M12, IP68
Enclosure construction	High quality, power coated, IP66 aluminium
Dimensions	160 x 129 x 61 mm
Weight	0.9kg
IP Rating	IP66
Certification	CE compliant
Accessories available	External mounting feet
Ordering Info	
PSU-VAR-20W	External PSU for Vario i2, 24V, 20W, 1xO/P, IP66